

# Radio Measurement and Test Report

For

**Shanxi Jianyu Science and technology co., LTD.**

**No.12 xin jin ci lu road hui jin garden 7th floor 4-201 Taiyuan city,**

**Shanxi Province**

**Test Standards:** ETSI EN 300 328 V2.1.1 (2016-11)

**Product Description:** bluetooth headset

**Tested Model:** JETBLUE HD1

**Report No.:** STR17068416E-1

**Tested Date:** 2017-06-13 to 2017-06-28

**Issued Date:** 2017-06-28

**Tested By:** Jason Su / Engineer

**Reviewed By:** Silin Chen / EMC Manager

**Approved & Authorized By:** Jandy So / PSQ Manager

**Prepared By:**

**Shenzhen SEM.Test Technology Co., Ltd.**

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,  
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

*Jason Su*  
*Silin Chen*  
*Jandy So*

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION.....</b>	<b>4</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY.....	5
1.5 EUT SETUP AND TEST MODE.....	6
1.6 MEASUREMENT UNCERTAINTY.....	7
1.7 TEST EQUIPMENT LIST AND DETAILS.....	7
<b>2. SUMMARY OF TEST RESULTS.....</b>	<b>8</b>
<b>3. RF OUTPUT POWER.....</b>	<b>9</b>
3.1 STANDARD APPLICABLE.....	9
3.2 TEST PROCEDURE.....	9
3.3 SUMMARY OF TEST RESULTS.....	10
<b>4. ACCUMULATED TRANSMIT TIME, FREQUENCY OCCUPATION AND HOPPING SEQUENCE.....</b>	<b>12</b>
4.1 STANDARD APPLICATION.....	12
4.2 TEST PROCEDURE.....	12
4.3 SUMMARY OF TEST RESULTS/PLOTS.....	14
<b>5. HOPPING FREQUENCY SEPARATION.....</b>	<b>19</b>
5.1 STANDARD APPLICATION.....	19
5.2 TEST PROCEDURE.....	19
5.3 SUMMARY OF TEST RESULTS/PLOTS.....	20
<b>6. POWER SPECTRAL DENSITY.....</b>	<b>23</b>
6.1 STANDARD APPLICABLE.....	23
6.2 TEST PROCEDURE.....	23
6.3 SUMMARY OF TEST RESULTS.....	24
<b>7. ADAPTIVITY (ADAPTIVE FREQUENCY HOPPING).....</b>	<b>25</b>
7.1 TEST EQUIPMENT LIST AND DETAILS.....	25
7.2 STANDARD APPLICATION.....	25
7.3 TEST PROCEDURE.....	26
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	26
<b>8. OCCUPIED CHANNEL BANDWIDTH.....</b>	<b>28</b>
8.1 STANDARD APPLICATION.....	28
8.2 TEST PROCEDURE.....	28
8.3 SUMMARY OF TEST RESULTS/PLOTS.....	28
<b>9. TRANSMITTER UNWANTED EMISSIONS IN THE OUT-OF-BAND DOMAIN.....</b>	<b>33</b>
9.1 STANDARD APPLICATION.....	33
9.2 TEST PROCEDURE.....	33
9.3 SUMMARY OF TEST RESULTS/PLOTS.....	35
<b>10. TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN.....</b>	<b>36</b>
10.1 STANDARD APPLICABLE.....	36
10.2 TEST PROCEDURE.....	36
10.3 SUMMARY OF TEST RESULTS/PLOTS.....	36
<b>11. RECEIVER SPURIOUS EMISSIONS.....</b>	<b>46</b>
11.1 STANDARD APPLICABLE.....	46
11.2 TEST PROCEDURE.....	46
11.3 SUMMARY OF TEST RESULTS/PLOTS.....	46
<b>12. RECEIVER BLOCKING.....</b>	<b>49</b>
12.1 STANDARD APPLICATION.....	49
12.2 TEST PROCEDURE.....	51
12.3 TEST PROCEDURE.....	52
12.4 SUMMARY OF TEST RESULTS/PLOTS.....	52
<b>EXHIBIT 1 - PRODUCT LABELING.....</b>	<b>54</b>

---

PROPOSED CE LABEL FORMAT .....	54
PROPOSED LABEL LOCATION ON EUT .....	54
<b>EXHIBIT 2 - EUT PHOTOGRAPHS.....</b>	<b>55</b>
<b>EXHIBIT 3 - TEST SETUP PHOTOGRAPHS .....</b>	<b>59</b>

SEM-Tes

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Manufacturer: Shanxi Jianyu Science and technology co., LTD.  
Address of manufacturer: No.12 xin jin ci lu road hui jin garden 7th floor 4-201 taiyuan city, Shanxi Province

#### General Description of EUT

Product Name:	bluetooth headset
Trade Name:	PRYME
Model No.:	Jetblue HD1
Adding Model(s):	/
Rated Voltage:	USB DC 5V ; Battery:DC3.7V
Power Adaptor Model:	/

*Note: The test data is gathered from a production sample, provided by the manufacturer.*

#### Technical Characteristics of EUT

Bluetooth Version:	V4.0
Frequency Range:	2402-2480MHz
RF Output Power:	10.894dBm (EIRP)
Type of Modulation:	GFSK, Pi/4 DQPSK, 8DPSK
Data Rate:	1Mbps, 2Mbps, 3Mbps
Quantity of Channels	79/40
Channel Separation:	1MHz/2MHz
Type of Antenna:	PCB
Antenna Gain:	2dBi
Equipment Type (Adaptivity):	Adaptive Equipment

## 1.2 Test Standards

The following report is prepared on behalf of the Shanxi Jianyu Science and technology co., LTD. in accordance with ETSI EN 300328, Electromagnetic compatibility and Radio spectrum Matters (ERM); Wideband transmission systems; Data transmission equipment operating in the 2,4 GHz ISM band and using wide band modulation techniques; Harmonized EN covering essential requirements under article 3.2 of the RED Directive.

The objective of the manufacturer is to demonstrate compliance with ETSI EN 300328.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission/immunity should be checked to ensure compliance has been maintained

## 1.3 Test Methodology

All measurements contained in this report were conducted with ETSI EN 300328, Electromagnetic compatibility and Radio spectrum Matters (ERM); Wideband transmission systems; Data transmission equipment operating in the 2,4 GHz ISM band and using wide band modulation techniques; Harmonized EN covering essential requirements under article 3.2 of the RED Directive.

## 1.4 Test Facility

### **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

### **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

### **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2<sup>nd</sup> Road, Bao'an District, Shenzhen, P.R.C (518101).

## 1.5 EUT Setup and Test Mode

The equipment under test (EUT) was configured to measure its highest possible emission/immunity level. The test modes were adapted according to the operation manual for use, the EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low Channel	2402MHz
TM2	Middle Channel	2441MHz
TM3	High Channel	2480MHz
TM4	Hopping	2402-2480MHz
TM5	GFSK(BLE)	2402MHz, 2442MHz, 2480MHz

Modulation Configure			
Modulation	Packet	Packet Type	Packet Size
GFSK	DH1	4	27
	DH3	11	183
	DH5	15	339
Pi/4 DQPSK	2DH1	20	54
	2DH3	26	367
	2DH5	30	379
8DPSK	3DH1	24	83
	3DH3	27	552
	3DH5	31	1021

Note: The bluetooth has been tested on the modulation of GFSK, (Pi/4)DQPSK and 8DPSK, compliance test and record the worst case.

Test Conditions					
	Normal	LTLV	LTHV	HTHV	HTLV
Temperature (°C )	20	-20	-20	55	55
Voltage (V)	3.7	3.3	4.1	4.1	3.3

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
USB Cable	0.2	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E10	LR-63C8R

## 1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	---	$\pm 1 \times 10^{-7}$
Power Spectral Density	Conducted	$\pm 0.70\text{dB}$
Transmitter Spurious Emissions	Radiated	$\pm 5.2\text{dB}$
Receiver Spurious Emissions	Radiated	$\pm 5.2\text{dB}$

## 1.7 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
Spectrum Analyzer	Agilent	N9020A	US47140102	2017-06-12	2018-06-11
Signal Generator	Agilent	83752A	3610A01453	2017-06-12	2018-06-11
Vector Signal Generator	Agilent	N5182A	MY47070202	2017-06-12	2018-06-11
Power Sensor	Agilent	U2021XA	MY54250019	2017-06-12	2018-06-11
Power Sensor	Agilent	U2021XA	MY54250021	2017-06-12	2018-06-11
Simultaneous Sampling	Agilent	U2531A	TW54243509	2017-06-12	2018-06-11
Spectrum Analyzer	Agilent	E4407B	MY41440400	2017-06-12	2018-06-11
Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2017-06-12	2018-06-11
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2017-06-12	2018-06-11
Amplifier	Agilent	8447F	3113A06717	2017-06-12	2018-06-11
Amplifier	C&D	PAP-1G18	2002	2017-06-12	2018-06-11
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2017-06-12	2018-06-11
Horn Antenna	ETS	3117	00086197	2017-06-12	2018-06-11
Temperature&Humidity Chamber	GONGWEN	GDJS-800	/	2017-06-12	2018-06-11
DC Power Supply	ATTEN	APS3005Dm	/	2017-06-12	2018-06-11
Universal Radio Communication Tester	Rohde & Schwarz	CMW500	/	2017-06-12	2018-06-11

## 2. SUMMARY OF TEST RESULTS

Standards	Reference	Description of Test Item	Result
EN 300328 V2.1.1(2016-11)	4.3.1.2 / 4.3.2.2	RF Output Power	Passed
	4.3.2.3	Power Spectral Density	Passed
	4.3.1.3 / 4.3.2.4	Duty Cycle, Tx-sequence, Tx-gap	N/A
	4.3.1.4	Accumulated Transmit Time, Frequency Occupation and Hopping Sequence	Passed
	4.3.1.5	Hopping Frequency Separation	Passed
	4.3.1.6 / 4.3.2.5	Medium Utilisation (MU) Factor	N/A
	4.3.1.7 / 4.3.2.6	Adaptivity (Adaptive Frequency Hopping)	Passed
	4.3.1.8 / 4.3.2.7	Occupied Channel Bandwidth	Passed
	4.3.1.9 / 4.3.2.8	Transmitter Unwanted Emissions in the Out-of-band Domain	Passed
	4.3.1.10 / 4.3.2.9	Transmitter Unwanted Emissions in the Spurious Domain	Passed
	4.3.1.11 / 4.3.2.10	Receiver Spurious Emissions	Passed
	4.3.1.12 / 4.3.2.11	Receiver Blocking	Passed
<p>Passed: The EUT complies with the essential requirements in the standard</p> <p>Failed: The EUT does not comply with the essential requirements in the standard</p> <p>N/A: not applicable</p>			



### 3. RF Output Power

---

#### 3.1 Standard Applicable

According to Section 4.3.1.2.3, The maximum RF output power for adaptive Frequency Hopping equipment shall be equal to or less than 20 dBm. The maximum RF output power for non-adaptive Frequency Hopping equipment, shall be declared by the supplier. The maximum RF output power for this equipment shall be equal to or less than the value declared by the supplier. This declared value shall be equal to or less than 20 dBm.

According to Section 4.3.2.2.3, For adaptive equipment using wide band modulations other than FHSS, the maximum RF output power shall be 20 dBm. The maximum RF output power for non-adaptive equipment shall be declared by the supplier and shall not exceed 20 dBm. For non-adaptive equipment using wide band modulations other than FHSS, the maximum RF output power shall be equal to or less than the value declared by the supplier.

#### 3.2 Test Procedure

According to section 5.3.2.2.1.1 of the standard EN 300328, the test procedure shall be as follows:

**Step 1:**

- Use a fast power sensor suitable for 2,4 GHz and capable of 1 MS/s.
- Use the following settings: - Sample speed 1 MS/s or faster.
- The samples must represent the power of the signal.
- Measurement duration: For non-adaptive equipment: equal to the observation period defined in clauses 4.3.1.2.1 or 4.3.2.3.1. For adaptive equipment, the measurement duration shall be long enough to ensure a minimum number of bursts (at least 10) are captured.

NOTE 1: For adaptive equipment, to increase the measurement accuracy, a higher number of bursts may be used.

**Step 2:**

- For conducted measurements on devices with one transmit chain:
  - Connect the power sensor to the transmit port, sample the transmit signal and store the raw data. Use these stored samples in all following steps.
- For conducted measurements on devices with multiple transmit chains:
  - Connect one power sensor to each transmit port for a synchronous measurement on all transmit ports.
  - Trigger the power sensors so that they start sampling at the same time. Make sure the time difference between the samples of all sensors is less than half the time between two samples.
  - For each individual sampling point (time domain), sum the coincident power samples of all ports and store them. Use these summed samples in all following steps..

**Step 3:**

- Find the start and stop times of each burst in the stored measurement samples.

The start and stop times are defined as the points where the power is at least 30 dB below the highest value of the stored samples in step 2.

NOTE 2: In case of insufficient dynamic range, the value of 30 dB may need to be reduced appropriately.

**Step 4:**

• Between the start and stop times of each individual burst calculate the RMS power over the burst using the formula below. Save these Pburst values, as well as the start and stop times for each burst.

$$P_{burst} = \frac{1}{k} \sum_{n=1}^k P_{sample}(n)$$

with 'k' being the total number of samples and 'n' the actual sample number

**Step 5:**

• The highest of all Pburst values (value "A" in dBm) will be used for maximum e.i.r.p. calculations.

**Step 6:**

- Add the (stated) antenna assembly gain "G" in dBi of the individual antenna.
- If applicable, add the additional beamforming gain "Y" in dB.
- If more than one antenna assembly is intended for this power setting, the maximum overall antenna gain (G or G + Y) shall be used.
- The RF Output Power (P) shall be calculated using the formula below:  $P = A + G + Y$
- This value, which shall comply with the limit given in clause 4.3.1.2.3 or clause 4.3.2.2.3, shall be recorded in the test report.

**3.3 Summary of Test Results**

Test Conditions	Measured Value	Antenna Gain	EIRP	Limit
	dBm	dBi	dBm	dBm
GFSK Lowest Channel (2402MHz)				
Normal	6.340	2	8.340	20
LTLV	6.337	2	8.337	20
LTHV	6.338	2	8.338	20
HTHV	6.336	2	8.336	20
HTLV	6.339	2	8.339	20
GFSK Middle Channel (2441MHz)				
Normal	8.219	2	10.219	20
LTLV	8.217	2	10.217	20
LTHV	8.216	2	10.216	20
HTHV	8.218	2	10.218	20
HTLV	8.215	2	10.215	20
GFSK Highest Channel (2480MHz)				
Normal	8.884	2	10.884	20
LTLV	8.883	2	10.883	20
LTHV	8.880	2	10.880	20
HTHV	8.882	2	10.882	20
HTLV	8.879	2	10.879	20
8DPSK Lowest Channel (2402MHz)				

Normal	6.285	2	8.285	20
LTLV	6.283	2	8.283	20
LTHV	6.281	2	8.281	20
HTHV	6.284	2	8.284	20
HTLV	6.280	2	8.280	20
8DPSK Middle Channel (2441MHz)				
Normal	8.152	2	10.152	20
LTLV	8.150	2	10.150	20
LTHV	8.149	2	10.149	20
HTHV	8.151	2	10.151	20
HTLV	8.148	2	10.148	20
8DPSK Highest Channel (2480MHz)				
Normal	8.872	2	10.872	20
LTLV	8.870	2	10.870	20
LTHV	8.871	2	10.871	20
HTHV	8.869	2	10.869	20
HTLV	8.868	2	10.868	20

Test Conditions	Measured Value	Antenna Gain	EIRP	Limit
	dBm	dBi	dBm	dBm
BLE Lowest Channel (2402MHz)				
Normal	7.956	2	9.956	20
LTLV	7.954	2	9.954	20
LTHV	7.953	2	9.953	20
HTHV	7.955	2	9.955	20
HTLV	7.951	2	9.951	20
BLE Middle Channel (2442MHz)				
Normal	8.894	2	10.894	20
LTLV	8.892	2	10.892	20
LTHV	8.893	2	10.893	20
HTHV	8.891	2	10.891	20
HTLV	8.890	2	10.890	20
BLE Highest Channel (2480MHz)				
Normal	8.577	2	10.577	20
LTLV	8.572	2	10.572	20
LTHV	8.576	2	10.576	20
HTHV	8.574	2	10.574	20
HTLV	8.573	2	10.573	20

## 4. Accumulated Transmit Time, Frequency Occupation and Hopping Sequence

### 4.1 Standard Application

According to section 4.3.1.4.3,

Adaptive Frequency Hopping equipment shall be capable of operating over a minimum of 70 % of the band specified in clause 1.

The Accumulated Transmit Time on any hopping frequency shall not be greater than 400 ms within any observation period of 400 ms multiplied by the minimum number of hopping frequencies (N) that have to be used.

In order for the equipment to comply with the Frequency Occupation requirement, it shall meet either of the following two options:

Option 1: Each hopping frequency of the hopping sequence shall be occupied at least once within a period not exceeding four times the product of the dwell time and the number of hopping frequencies in use.

Option 2: The occupation probability for each frequency shall be between  $((1 / U) \times 25 \%)$  and 77 % where U is the number of hopping frequencies in use.

The hopping sequence(s) shall contain at least N hopping frequencies at all times, where N is 15 or 15 divided by the minimum Hopping Frequency Separation in MHz, whichever is the greater.

### 4.2 Test procedure

According to section 5.3.4.2.1, the test procedure shall be as follows:

#### Step 1:

- The output of the transmitter shall be connected to a spectrum analyzer or equivalent.
- The analyzer shall be set as follows:
  - Centre Frequency: Equal to the hopping frequency being investigated
  - Frequency Span: 0 Hz
  - RBW:  $\sim 50 \%$  of the Occupied Channel Bandwidth
  - VBW:  $\geq$  RBW
  - Detector Mode: RMS
  - Sweep time: Equal to the applicable observation period (see clause 4.3.1.4.3.1 or clause 4.3.1.4.3.2)
  - Number of sweep points: 30 000
  - Trace mode: Clear / Write
  - Trigger: Free Run

#### Step 2:

- Save the trace data to a file for further analysis by a computing device using an appropriate software application or program.

#### Step 3:

- Identify the data points related to the frequency being investigated by applying a threshold.

The data points resulting from transmissions on the hopping frequency being investigated are assumed to have much higher levels compared to data points resulting from transmissions on adjacent hopping frequencies. If a clear determination between these transmissions is not possible, the RBW in step 1 shall be further reduced. In

addition, a channel filter may be used.

- Count the number of data points identified as resulting from transmissions on the frequency being investigated and multiply this number by the time difference between two consecutive data points.

**Step 4:**

- The result in step 3 is the accumulated Dwell Time which shall comply with the limit provided in clauses 4.3.1.4.3.1 or 4.3.1.4.3.2 and which shall be recorded in the test report.

**Step 5:**

NOTE 1: This step is only applicable for equipment implementing Option 1 in clause 4.3.1.4.3.1 or clause 4.3.1.4.3.2 for complying with the Frequency Occupation requirement and the manufacturer decides to demonstrate compliance with this requirement via measurement.

- Make the following changes on the analyser and repeat step 2 and step 3.

Sweep time:  $4 \times \text{Dwell Time} \times \text{Actual number of hopping frequencies in use}$

The hopping frequencies occupied by the equipment without having transmissions during the dwell time (blacklisted frequencies) should be taken into account in the actual number of hopping frequencies in use. If this number cannot be determined (number of blacklisted frequencies unknown) it shall be assumed that the equipment uses the maximum possible number of hopping frequencies.

- The result shall be compared to the limit for the Frequency Occupation defined in clause 4.3.1.4.3.1 or clause 4.3.1.4.3.2. The result of this comparison shall be recorded in the test report.

**Step 6:**

- Make the following changes on the analyzer:

- Start Frequency: 2 400 MHz
- Stop Frequency: 2 483,5 MHz
- RBW:  $\sim 50\%$  of the Occupied Channel Bandwidth (single hopping frequency)
- VBW:  $\geq$  RBW
- Detector Mode: RMS
- Sweep time: 1s
- Trace Mode: Max Hold
- Trigger: Free Run

NOTE 2: The above sweep time setting may result in long measuring times. To avoid such long measuring times, an FFT analyser could be used.

- Wait for the trace to stabilize. Identify the number of hopping frequencies used by the hopping sequence.
- The result shall be compared to the limit (value N) defined in clause 4.3.1.4.3.1 or clause 4.3.1.4.3.2. This value shall be recorded in the test report.

For equipment with blacklisted frequencies, it might not be possible to verify the number of hopping frequencies in use. However they shall comply with the requirement for Accumulated Transmit Time and Frequency Occupation assuming the minimum number of hopping frequencies (N) defined in clause 4.3.1.4.3.1 or clause 4.3.1.4.3.2 is used.

**Step 7:**

- For adaptive systems, using the lowest and highest -20 dB points from the total spectrum envelope obtained in

step 6, it shall be verified whether the system uses 70 % of the band specified in clause 1. The result shall be recorded in the test report.

RBW/RBW=500/500kHz

### 4.3 Summary of Test Results/Plots

Test data is corrected with the worse case, which the packet length is DH5


Modulation	Test Channel	Packet	Maximum Accumulated Dwell Time		
			Time Slot Length	Acc. Dwell Time	Limit
			ms	ms	ms
GFSK	2402MHz	DH5	2.88	307.200	400
	2441MHz	DH5	2.89	308.267	400
	2480MHz	DH5	2.89	308.267	400
Test Period: 400ms X Minimum number of hopping frequencis (N)					
Accumulated Dwell Time = Time slot length (Dwell time) X Number of data points within a test period					

Modulation	Test Channel	Packet	Minimum Frequency Occupation Time		
			Time Slot Length	Occupation Time	Limit
			ms	ms	ms
GFSK	2402MHz	DH1	0.380	486.400	400
	2441MHz	DH1	0.380	486.400	400
	2480MHz	DH1	0.380	486.400	400
Test Period: 4 X Dwell time X Minimum number of hopping frequencis (N)					
Occupation Time = Time slot length (Dwell time) X Number of data points within a test period					


Frequency Band	Number of Hopping Frequencies (N)	Limit	Result
2400-2483.5MHz	79	15	Pass
	-20dB Points Occupied Bandwidth	Limit	Result
	80.126	58.45MHz = 70% X 83.5MHz	Pass

Please refer to the test plots as below:


## Dwell time-DH1-Low Channel




## Dwell time-DH1-Middle Channel



## Dwell time-DH1-High Channel




## Dwell time-DH5-Low Channel







## Dwell time-DH5-Middle Channel




## Dwell time-DH5-High Channel



-20dB Bandwidth



Channel No.



## 5. Hopping Frequency Separation

### 5.1 Standard Application

According to section 4.3.1.5.3,

For adaptive Frequency Hopping equipment, the minimum Hopping Frequency Separation shall be 100 kHz.

Adaptive Frequency Hopping equipment, which for one or more hopping frequencies, has switched to a non-adaptive mode because interference was detected on all these hopping positions with a level above the threshold level defined in clause 4.3.1.7.2.2 or clause 4.3.1.7.3.2, is allowed to continue to operate with a minimum Hopping Frequency Separation of 100 kHz on these hopping frequencies as long as the interference is present on these frequencies. The equipment shall continue to operate in an adaptive mode on other hopping frequencies.

Adaptive Frequency Hopping equipment which decided to operate in a non-adaptive mode on one or more hopping frequencies without the presence of interference, shall comply with the limit in clause 4.3.1.5.3.1 for these hopping frequencies as well as with all other requirements applicable to non-adaptive frequency hopping equipment.

### 5.2 Test procedure

According to the section 5.3.5.2.1, the option 2 test method shall be used.

#### Step 1:

The output of the transmitter shall be connected to a spectrum analyzer or equivalent.

The analyzer shall be set as follows:

- Centre Frequency: Centre of the two adjacent hopping frequencies
- Frequency Span: Sufficient to see the complete power envelope of both hopping frequencies
- RBW: 1 % of the Span
- VBW:  $3 \times \text{RBW}$
- Detector Mode: RMS
- Trace Mode: Max Hold
- Sweep Time: 1s

NOTE: Depending on the nature of the signal (modulation), it might be required to use a much longer sweep time, e.g. in case switching transients are present in the signals to be investigated.

#### Step 2:

- Wait for the trace to stabilize.
- Use the marker-delta function to determine the Hopping Frequency Separation between the centres of the two adjacent hopping frequencies (e.g. by indentifying peaks or notches at the centre of the power envelope for the two adjacent signals). This value shall be compared with the limits defined in clause 4.3.1.5.3 and shall be recorded in the test report.

RBW/VBW=30/100kHz

### 5.3 Summary of Test Results/Plots


Test Mode	Test Channel	Adjacent Channel	Channel SeapARATION	Limit
	MHz	MHz	kHz	kHz
GFSK	2402	2403	1005.0	100
	2480	2479	1005.0	100
8DPSK	2402	2403	1005.0	100
	2480	2479	1005.0	100

Please refer to the following test plots:


EM Test

For GFSK

Channel spacing-Lowest channel




Channel spacing-Highest channel




For 8DPSK

Channel spacing-Lowest channel



For 8DPSK

Channel spacing-Lowest channel



## 6. Power Spectral Density

### 6.1 Standard Applicable

According to Section 4.3.2.3.3, For equipment using wide band modulations other than FHSS, the maximum Power Spectral Density is limited to 10 dBm per MHz.

### 6.2 Test Procedure

According to section 5.3.3.2.1 of the standard EN 300328, the test procedure shall be as follows:

#### Step 1:

Connect the UUT to the spectrum analyser and use the following settings:

- Start Frequency: 2 400 MHz
- Stop Frequency: 2 483,5 MHz
- Resolution BW: 10 kHz
- Video BW: 30 kHz
- Sweep Points: > 8 350

NOTE: For spectrum analysers not supporting this number of sweep points, the frequency band may be segmented.

- Detector: RMS
- Trace Mode: Max Hold
- Sweep time: 10 s; the sweep time may be increased further until a value where the sweep time has no impact on the RMS value of the signal

For non-continuous signals, wait for the trace to stabilize.

Save the data (trace data) set to a file.

#### Step 2:

For conducted measurements on smart antenna systems using either operating mode 2 or operating mode 3 (see clause 5.1.3.2), repeat the measurement for each of the transmit ports. For each sampling point (frequency domain), add up the coincident power values (in mW) for the different transmit chains and use this as the new data set.

#### Step 3:

Add up the values for power for all the samples in the file using the formula below.

$$P_{Sum} = \sum_{n=1}^k P_{sample}(n)$$

with 'k' being the total number of samples and 'n' the actual sample number

#### Step 4:

Normalize the individual values for power (in dBm) so that the sum is equal to the RF Output Power (e.i.r.p.) measured in clause 5.3.2 and save the corrected data. The following formulas can be used:

$$C_{Corr} = P_{Sum} - P_{e.i.r.p.}$$

$$P_{Samplecorr}(n) = P_{Sample}(n) - C_{Corr}$$

with 'n' being the actual sample number

### Step 5:

Starting from the first sample  $P_{\text{Samplecorr}}(n)$  (lowest frequency), add up the power (in mW) of the following samples representing a 1 MHz segment and record the results for power and position (i.e. sample #1 to sample #100). This is the Power Spectral Density (e.i.r.p.) for the first 1 MHz segment which shall be recorded.

### Step 6:

Shift the start point of the samples added up in step 5 by one sample and repeat the procedure in step 5 (i.e. sample #2 to sample #101).

### Step 7:

Repeat step 6 until the end of the data set and record the Power Spectral Density values for each of the 1 MHz segments.

From all the recorded results, the highest value is the maximum Power Spectral Density for the UUT. This value, which shall comply with the limit given in clause 4.3.2.3.3, shall be recorded in the test report.

RBW/VBW=10/30 kHz

## 6.3 Summary of Test Results

Test Mode	Test Frequency	Reading	Antenna Gain	Spectral Density	Limit
	MHz	dBm/MHz	dBi	dBm/MHz	dBm/MHz
BLE	2402	-6.198	2	-4.198	10
	2442	-5.405	2	-3.405	10
	2480	-4.810	2	-2.810	10



## 7. Adaptivity (Adaptive Frequency Hopping)

### 7.1 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2014-05-28	2015-05-27
Attenuator	ATTEN	ATS100-4-20	/	2014-05-28	2015-05-27
Power Divider	Weinschel	1506A	PM204	2014-05-28	2015-05-27
Signal Generator	Rohde & Schwarz	SMR20	100047	2014-05-28	2015-05-27

### 7.2 Standard Application

According to section 4.3.1.6.2, Adaptive Frequency Hopping equipment using LBT based DAA shall comply with the following minimum set of requirements:


- 1) At the start of every dwell time, before transmission on a hopping frequency, the equipment shall perform a Clear Channel Assessment (CCA) check using energy detect. The CCA observation time shall be not less than 0,2 % of the Channel Occupancy Time (see step 3) with a minimum of 20  $\mu$ s. If the equipment finds the hopping frequency to be clear, it may transmit immediately (see step 3).
- 2) If it is determined that a signal is present with a level above the detection threshold defined in step 5. the hopping frequency shall be marked as 'unavailable'. Then the equipment may jump to the next frequency in the hopping scheme even before the end of the dwell time, but in that case the 'unavailable' channel can not be considered as being 'occupied' and shall be disregarded with respect to the requirement to maintain a minimum of 15 hopping frequencies. Alternatively, the equipment can remain on the frequency during the remainder of the dwell time. However, if the equipment remains on the frequency with the intention to transmit, it shall perform an extended CCA check in which the (unavailable) channel is observed for a random duration between the value defined for the CCA observation time in step 1 and 5 % of the Channel Occupancy Time defined in step 3. If the extended CCA check has determined the frequency to be no longer occupied, the hopping frequency becomes available again. The CCA observation time used by the equipment shall be declared by the supplier.
- 3) The total time during which an equipment has transmissions on a given hopping frequency without re-evaluating the availability of that frequency is defined as the Channel Occupancy Time.  
  
The Channel Occupancy Time for a given hopping frequency, which starts immediately after a successful CCA, shall be less than 60 ms followed by an Idle Period of minimum 5 % of the Channel Occupancy Time with a minimum of 100  $\mu$ s. After this, the procedure as in step 1 shall be repeated before having new transmissions on this hopping frequency during the same dwell time.
- 4) 'Unavailable' channels may be removed from or may remain in the hopping sequence, but in any case:
  - there shall be no transmissions on 'unavailable' channels;
  - a minimum of 15 hopping frequencies shall always be maintained.

5) The detection threshold shall be proportional to the transmit power of the transmitter: for a 20 dBm e.i.r.p. transmitter the detection threshold level (TL) shall be equal or lower than -70 dBm/MHz at the input to the receiver (assuming a 0 dBi receive antenna). For power levels below 20 dBm e.i.r.p., the detection threshold level may be relaxed to  $TL = -70 \text{ dBm/MHz} + 20 - P_{out} \text{ e.i.r.p.}$  ( $P_{out}$  in dBm).

If implemented, Short Control Signalling Transmissions shall have a maximum duty cycle of 10 % within an observation period of 50 ms or within an observation period equal to the dwell time, whichever is the shorter.

### 7.3 Test procedure

According to the section 5.3.7.2.1, the test block diagram shall be used.



All test procedure is carried to the section 5.3.7.2.1

### 7.4 Summary of Test Results/Plots

Test Item	Limit	Measured Value	Result
Clear Channel Assessment (CCA)	>20us & 0.2%COT	135.00us	Pass
Extended CCA	/	/	Pass
Channel Occupancy Time (COT)	<60ms	14.57ms	Pass
Idle Period	>100us & 5%COT	1.04ms	Pass
No Transmission on 'Unavailable' Channels	Yes	Yes	Pass
Quantity of Hopping Frequency	15	16	Pass
Detection Thershold Level (TL)	-70dBm/MHz	-80.84dBm/MHz	Pass
Short Control Signalling Transmissions	<10% (Duty Cycle)	/	Pass

## 8. Occupied Channel Bandwidth

---

### 8.1 Standard Application

According to section 4.3.1.8.3. The Occupied Channel Bandwidth for each hopping frequency shall fall completely within the band given in clause 1.

For non-adaptive Frequency Hopping equipment with e.i.r.p greater than 10 dBm, the Occupied Channel Bandwidth for every occupied hopping frequency shall be equal to or less than the value declared by the supplier. This declared value shall not be greater than 5 MHz.

According to section 4.3.2.7.3. The Occupied Channel Bandwidth shall fall completely within the band given in clause 1. In addition, for non-adaptive systems using wide band modulations other than FHSS and with e.i.r.p greater than 10 dBm, the occupied channel bandwidth shall be less than 20 MHz.

### 8.2 Test procedure

According to the section 5.3.8.2.1, the measurement procedure shall be as follows:

#### Step 1:

Connect the UUT to the spectrum analyser and use the following settings:

- Centre Frequency: The centre frequency of the channel under test
- Resolution BW:  $\sim 1\%$  of the span without going below  $1\%$
- Video BW:  $3 \times \text{RBW}$
- Frequency Span for frequency hopping equipment: Lowest frequency separation that is used within the hopping sequence
- Frequency Span for other types of equipment:  $2 \times \text{Nominal Channel Bandwidth}$  (e.g. 40 MHz for a 20 MHz channel)
- Detector Mode: RMS
- Trace Mode: Max Hold
- Sweep time: 1 s

#### Step 2:

Wait until the trace is completed.

Find the peak value of the trace and place the analyser marker on this peak.

#### Step 3:

Use the 99 % bandwidth function of the spectrum analyser to measure the Occupied Channel Bandwidth of the UUT. This value shall be recorded.

### 8.3 Summary of Test Results/Plots

Test Mode	Test Channel	Measured Value	Result
	MHz	kHz	
GFSK	2402	845.1601	Pass
	2480	841.7706	Pass
8DPSK	2402	1164.2	Pass
	2480	1182.6	Pass
BLE	2402	1025.8	Pass
	2480	1025.1	Pass


Please refer to the test plots as below:

EMT TEST


### Lowest Channel (GFSK)




### Highest Channel (GFSK)




### Lowest Channel (8DPSK)




### Highest Channel (8DPSK)



BLE-low



BLE-High






## 9. Transmitter Unwanted Emissions in the Out-of-band Domain

### 9.1 Standard Application

According to section 4.3.1.9.3&4.3.2.8.3, The transmitter unwanted emissions in the out-of-band domain but outside the allocated band, shall not exceed the values provided by the mask in figure below



Within the 2 400 MHz to 2 483,5 MHz band, the Out-of-band emissions are fulfilled by compliance with the Occupied Channel Bandwidth requirement

### 9.2 Test procedure

According to the section 5.3.9.2.1, the measurement procedure shall be as follows:

The Out-of-band emissions within the different horizontal segments of the mask provided in figures 1 and 3 shall be measured using the steps below. This method assumes the spectrum analyser is equipped with the Time Domain Power option.

#### Step 1:

- Connect the UUT to the spectrum analyser and use the following settings:
  - Centre Frequency: 2 484 MHz
  - Span: 0 Hz
  - Resolution BW: 1 MHz
  - Filter mode: Channel filter
  - Video BW: 3 MHz
  - Detector Mode: RMS
  - Trace Mode: Max Hold
  - Sweep Mode: Continuous
  - Sweep Points: Sweep Time [s] / (1  $\mu$  s) or 5 000 whichever is greater
  - Trigger Mode: Video trigger

NOTE 1: In case video triggering is not possible, an external trigger source may be used.

- Sweep Time: > 120 % of the duration of the longest burst detected during the measurement of the RF Output Power

**Step 2:** (segment  $2\,483,5\text{ MHz}$  to  $2\,483,5\text{ MHz} + \text{BW}$ )

- Adjust the trigger level to select the transmissions with the highest power level.
- For frequency hopping equipment operating in a normal hopping mode, the different hops will result in signal bursts with different power levels. In this case the burst with the highest power level shall be selected.
- Set a window (start and stop lines) to match with the start and end of the burst and in which the RMS power shall be measured using the Time Domain Power function.
- Select RMS power to be measured within the selected window and note the result which is the RMS power within this 1 MHz segment ( $2\,483,5\text{ MHz}$  to  $2\,484,5\text{ MHz}$ ). Compare this value with the applicable limit provided by the mask.
- Increase the centre frequency in steps of 1 MHz and repeat this measurement for every 1 MHz segment within the range  $2\,483,5\text{ MHz}$  to  $2\,483,5\text{ MHz} + \text{BW}$ . The centre frequency of the last 1 MHz segment shall be set to  $2\,483,5\text{ MHz} + \text{BW} - 0,5\text{ MHz}$  (which means this may partly overlap with the previous 1 MHz segment).

**Step 3:** (segment  $2\,483,5\text{ MHz} + \text{BW}$  to  $2\,483,5\text{ MHz} + 2\text{BW}$ )

- Change the centre frequency of the analyser to  $2\,484\text{ MHz} + \text{BW}$  and perform the measurement for the first 1 MHz segment within range  $2\,483,5\text{ MHz} + \text{BW}$  to  $2\,483,5\text{ MHz} + 2\text{BW}$ . Increase the centre frequency in 1 MHz steps and repeat the measurements to cover this whole range. The centre frequency of the last 1 MHz segment shall be set to  $2\,483,5\text{ MHz} + 2\text{BW} - 0,5\text{ MHz}$ .

**Step 4:** (segment  $2\,400\text{ MHz} - \text{BW}$  to  $2\,400\text{ MHz}$ )

- Change the centre frequency of the analyser to  $2\,399,5\text{ MHz}$  and perform the measurement for the first 1 MHz segment within range  $2\,400\text{ MHz} - \text{BW}$  to  $2\,400\text{ MHz}$ . Reduce the centre frequency in 1 MHz steps and repeat the measurements to cover this whole range. The centre frequency of the last 1 MHz segment shall be set to  $2\,400\text{ MHz} - 2\text{BW} + 0,5\text{ MHz}$ .

**Step 5:** (segment  $2\,400\text{ MHz} - 2\text{BW}$  to  $2\,400\text{ MHz} - \text{BW}$ )

- Change the centre frequency of the analyser to  $2\,399,5\text{ MHz} - \text{BW}$  and perform the measurement for the first 1 MHz segment within range  $2\,400\text{ MHz} - 2\text{BW}$  to  $2\,400\text{ MHz} - \text{BW}$ . Reduce the centre frequency in 1 MHz steps and repeat the measurements to cover this whole range. The centre frequency of the last 1 MHz segment shall be set to  $2\,400\text{ MHz} - 2\text{BW} + 0,5\text{ MHz}$ .

**Step 6:**

- In case of conducted measurements on equipment with a single transmit chain, the declared antenna assembly gain "G" in dBi shall be added to the results for each of the 1 MHz segments and compared with the limits provided by the mask given in figure 1 or figure 3. If more than one antenna assembly is intended for this power setting, the antenna with the highest gain shall be considered.
- In case of conducted measurements on smart antenna systems (equipment with multiple transmit chains), the measurements need to be repeated for each of the active transmit chains. The declared antenna assembly gain "G" in dBi for a single antenna shall be added to these results. If more than one antenna assembly is intended for this power setting, the antenna with the highest gain shall be considered. Comparison with the applicable limits shall be done using any of the options given below:
  - Option 1: the results for each of the transmit chains for the corresponding 1 MHz segments shall be added. The additional beamforming gain "Y" in dB shall be added as well and the resulting values

compared with the limits provided by the mask given in figure 1 or figure 3.

NOTE 2: A ch refers to the number of active transmit chains.

It shall be recorded whether the equipment complies with the mask provided in figure 1 or figure 3.

RBW=1MHz VBW=3MHz

### 9.3 Summary of Test Results/Plots

Test CH.	Test Segment	Max. Emissions Reading (dBm)					Limit
	MHz	Normal	LTLV	LTHV	HTHV	HTLV	dBm
Test Mode: <input type="checkbox"/> GFSK							
Lowest	2400-BW to 2400	-26.25	-25.62	-25.25	-24.23	-25.07	-10
	2400-2BW to 2400-BW	-42.26	-40.22	-40.05	-40.01	-41.66	-20
Highest	2483.5 to 2483.5+BW	-27.22	-26.29	-25.76	-25.31	-25.64	-10
	2483.5+BW to 2483.5+2BW	-43.46	-40.31	-40.20	-41.33	-42.20	-20
Note: BW = ( 0.845 ) MHz							
Test Mode: <input type="checkbox"/> GFSK (BLE)							
Lowest	2400-BW to 2400	-34.7	-34.5	-34.1	-34.9	-34.2	-10
	2400-2BW to 2400-BW	-44.0	-45.2	-45.3	-45.1	-44.3	-20
Highest	2483.5 to 2483.5+BW	-36.6	-33.9	-34.1	-34.2	-34.1	-10
	2483.5+BW to 2483.5+2BW	-44.2	-45.1	-43.2	-44.1	-44.7	-20
Note: BW = ( 1.03 ) MHz							

## 10. Transmitter Unwanted Emissions in the Spurious Domain

### 10.1 Standard Applicable

According to section 4.3.1.10.3& 4.3.2.9.3

The transmitter unwanted emissions in the spurious domain shall not exceed the values given in the following table.

Frequency range	Maximum power	Bandwidth
30 MHz to 47 MHz	-36 dBm	100 kHz
47 MHz to 74 MHz	-54 dBm	100 kHz
74 MHz to 87,5 MHz	-36 dBm	100 kHz
87,5 MHz to 118 MHz	-54 dBm	100 kHz
118 MHz to 174 MHz	-36 dBm	100 kHz
174 MHz to 230 MHz	-54 dBm	100 kHz
230 MHz to 470 MHz	-36 dBm	100 kHz
470 MHz to 862 MHz	-54 dBm	100 kHz
862 MHz to 1 GHz	-36 dBm	100 kHz
1 GHz to 12,75 GHz	-30 dBm	1 MHz


### 10.2 Test Procedure

The device under test has an integral antenna and the radiated measurement shall apply to the device, using the method of measurement as described in the EN300328 section 5.3.10.2.

RBW=100kHz    VBW=300kHz    30MHz-1GHz  
RBW=1MHz    VBW=3MHz    1GHz-12.75GHz


### 10.3 Summary of Test Results/Plots

According to the data, the EUT complied with the EN 300328 standards, and had the worst cases:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	49.0145	-83.24	4.36	-78.88	-54.00	-24.88	ERP
2	210.0482	-83.59	2.82	-80.77	-54.00	-26.77	ERP
3	506.4791	-83.16	10.64	-72.52	-54.00	-18.52	ERP


Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	56.5929	-84.32	3.59	-80.73	-54.00	-26.73	ERP
2	105.6415	-83.64	2.22	-81.42	-54.00	-27.42	ERP
3	916.0687	-84.04	17.35	-66.69	-36.00	-30.69	ERP


Test Mode: Transmitting-Highest channel

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	39.1616	-84.52	3.18	-81.34	-36.00	-45.34	ERP
2	47.6586	-83.55	4.34	-79.21	-54.00	-25.21	ERP
3	965.5421	-83.71	17.96	-65.75	-36.00	-29.75	ERP

Vertical:




No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	38.8879	-82.95	3.13	-79.82	-36.00	-43.82	ERP
2	49.5328	-83.23	4.35	-78.88	-54.00	-24.88	ERP
3	945.4399	-83.45	17.68	-65.77	-36.00	-29.77	ERP




Test Mode: Transmitting-Lowest channel(BLE)

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	47.4918	-83.14	4.35	-78.79	-54.00	-24.79	ERP
2	59.4405	-83.44	2.90	-80.54	-54.00	-26.54	ERP
3	92.4624	-83.01	1.11	-81.90	-54.00	-27.90	ERP


Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	47.4918	-83.14	4.35	-78.79	-54.00	-24.79	ERP
2	61.9951	-83.42	2.45	-80.97	-54.00	-26.97	ERP
3	108.6470	-83.72	2.20	-81.52	-54.00	-27.52	ERP


Test Mode: Transmitting-Highest channel(BLE)

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	47.3255	-85.26	4.35	-80.91	-54.00	-26.91	ERP
2	108.6470	-85.53	2.20	-83.33	-54.00	-29.33	ERP
3	495.9344	-84.16	10.58	-73.58	-54.00	-19.58	ERP

Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	47.3255	-83.97	4.35	-79.62	-54.00	-25.62	ERP
2	467.2349	-84.80	9.93	-74.87	-36.00	-38.87	ERP
3	881.4067	-83.79	16.81	-66.98	-36.00	-30.98	ERP

### Spurious Emission Above 1GHz

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Lowest Channel-2402MHz						
4804	-48.87	7.84	-41.03	-30	-11.03	H
7206	-56.24	12.78	-43.46	-30	-13.46	H
4804	-48.10	7.84	-40.26	-30	-10.26	V
7206	-57.43	12.78	-44.65	-30	-14.65	V
Highest Channel-2480MHz						
4960	-49.57	8.35	-41.22	-30	-11.22	H
7440	-58.52	13.97	-44.55	-30	-14.55	H
4960	-49.04	8.35	-40.69	-30	-10.69	V
7440	-58.14	12.78	-44.36	-30	-14.36	V

For BLE

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Lowest Channel-2402MHz						
4804	-42.87	7.84	-40.03	-30	-10.03	H
7206	-56.24	12.78	-43.46	-30	-13.46	H
4804	-47.10	7.84	-39.26	-30	-9.26	V
7206	-57.43	12.78	-44.65	-30	-14.65	V
Highest Channel-2480MHz						
4960	-48.57	8.35	-40.22	-30	-10.22	H
7440	-57.52	13.97	-43.55	-30	-13.55	H
4960	-48.04	8.35	-39.69	-30	-9.69	V
7440	-57.14	12.78	-43.36	-30	-13.36	V

Note 1: Testing is carried out with frequency rang 30MHz to 12.75GHz, which above 4<sup>th</sup> Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Note 2: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.  
And The worst case of EDR mode is 3DH1

## 11. Receiver Spurious Emissions

### 11.1 Standard Applicable

According to section 4.3.1.11.3&4.3.2.10.3, The spurious emissions of the receiver shall not exceed the values given in table below

NOTE: In case of equipment with antenna connectors, these limits apply to emissions at the antenna port (conducted) and to the emissions radiated by the cabinet. In case of integral antenna equipment (without temporary antenna connectors), these limits apply to emissions radiated by the equipment. Spurious emission limits for receivers

Frequency range	Maximum power e.r.p. ( $\leq 1$ GHz) e.i.r.p. ( $> 1$ GHz)	Measurement bandwidth
30 MHz to 1 GHz	-57 dBm	100 kHz
1 GHz to 12,75 GHz	-47 dBm	1 MHz

### 11.2 Test Procedure

The device under test has an integral antenna and the radiated measurement shall apply to the device, using the method of measurement as described in the EN300328 section 5.3.11.2.


RBW=100kHz    VBW=300kHz    30MHz-1GHz  
RBW=1MHz    VBW=3MHz    1GHz-12.75GHz

### 11.3 Summary of Test Results/Plots

According to the data, the EUT complied with the EN 300328 standards, and had the worst case:


Test Mode: Receiving

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	47.8260	-82.62	4.34	-78.28	-57.00	-21.28	ERP
2	55.4147	-82.26	3.81	-78.45	-57.00	-21.45	ERP
3	104.1701	-82.92	2.22	-80.70	-57.00	-23.70	ERP

Vertical



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	52.2079	-71.10	-7.66	-78.76	-57.00	-21.76	ERP
2	554.8254	-72.46	0.24	-72.22	-57.00	-15.22	ERP
3	919.2866	-75.58	5.59	-69.99	-57.00	-12.99	ERP

Frequency (MHz)	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
1994.00	-55.38	-47	-8.38	H
3013.00	-63.08	-47	-16.08	H
4342.00	-64.62	-47	-17.62	V
5856.00	-60.77	-47	-13.77	V

Note: Testing is carried out with frequency rang 30MHz to 12.75GHz, which above 1GHz are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



## 12. Receiver Blocking

---

### 12.1 Standard Application

According to section 4.3.2.11.2, Receiver blocking is a measure of the ability of the equipment to receive a wanted signal on its operating channel without exceeding a given degradation in the presence of an unwanted signal (blocking signal) at frequencies other than those of the operating band.

Load Based Equipment not using any of the mechanisms referenced above shall comply with the following minimum set of requirements :

The minimum performance criterion shall be a PER less than or equal to 10 %. The manufacturer may declare alternative performance criteria as long as that is appropriate for the intended use of the equipment (see clause 5.4.1.t)).

While maintaining the minimum performance criteria as defined in clause 4.3.2.11.3, the blocking levels at specified frequency offsets shall be equal to or greater than the limits defined for the applicable receiver category 1, 2 and 3 provided in table 14, table 15 or table 16.

#### 4.2.3.2.1 Receiver category 1

Adaptive equipment with a maximum RF output power greater than 10 dBm e.i.r.p. shall be considered as receiver category 1 equipment.

#### 4.2.3.2.2 Receiver category 2

Non-adaptive equipment with a Medium Utilization (MU) factor greater than 1 % and less than or equal to 10 % or adaptive equipment with a maximum RF output power of 10 dBm e.i.r.p. shall be considered as receiver category 2 equipment.

#### 4.2.3.2.3 Receiver category 3

Non-adaptive equipment with a maximum Medium Utilization (MU) factor of 1 % or adaptive equipment with a maximum RF output power of 0 dBm e.i.r.p. shall be considered as receiver category 3 equipment.

**Table 14: Receiver Blocking parameters for Receiver Category 1 equipment**

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Type of blocking signal
$P_{min} + 6 \text{ dB}$	2 380 2 503,5	-53	CW
$P_{min} + 6 \text{ dB}$	2 300 2 330 2 360	-47	CW
$P_{min} + 6 \text{ dB}$	2 523,5 2 553,5 2 583,5 2 613,5 2 643,5 2 673,5	-47	CW
NOTE: $P_{min}$ is the minimum level of the wanted signal (in dBm) required to meet the minimum performance criteria as defined in clause 4.3.2.11.3 in the absence of any blocking signal.			

**Table 15: Receiver Blocking parameters receiver category 2 equipment**

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Type of blocking signal
$P_{min} + 6 \text{ dB}$	2 380 2 503,5	-57	CW
$P_{min} + 6 \text{ dB}$	2 300 2 583,5	-47	CW
NOTE: $P_{min}$ is the minimum level of the wanted signal (in dBm) required to meet the minimum performance criteria as defined in clause 4.3.2.11.3 in the absence of any blocking signal.			

**Table 16: Receiver Blocking parameters receiver category 3 equipment**

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Type of blocking signal
$P_{min} + 12 \text{ dB}$	2 380 2 503,5	-57	CW
$P_{min} + 12 \text{ dB}$	2 300 2 583,5	-47	CW
NOTE: $P_{min}$ is the minimum level of the wanted signal (in dBm) required to meet the minimum performance criteria as defined in clause 4.3.2.11.3 in the absence of any blocking signal.			

## 12.2 Test Procedure

Step 1: • For non-frequency hopping equipment, the UUT shall be set to the lowest operating channel.

Step 2: • The blocking signal generator is set to the first frequency as defined in the appropriate table corresponding to the receiver category and type of equipment.

Step 3: • With the blocking signal generator switched off, a communication link is established between the UUT and the associated companion device using the test setup shown in figure 6. The variable attenuator is set to a value that achieves the minimum performance criteria as specified in clause 4.3.1.12.3 or clause 4.3.2.11.3 with a resolution of at least 1 dB. The resulting level for the wanted signal at the input of the UUT is  $P_{min}$ . This value shall be measured and recorded in the test report.

- The signal level is increased by the value provided in the table corresponding to the receiver category and type of equipment.

Step 4: • The blocking signal at the UUT is set to the level provided in the table corresponding to the receiver category and type of equipment. It shall be verified and recorded in the test report that the performance criteria as specified in clause 4.3.1.12.3 or clause 4.3.2.11.3 is met.

Step 5: • Repeat step 4 for each remaining combination of frequency and level for the blocking signal as provided in the table corresponding to the receiver category and type of equipment.

Step 6: • For non-frequency hopping equipment, repeat step 2 to step 5 with the UUT operating at the highest operating channel.

## 12.3 Test procedure

According to the section 5.4.11.2.1, the test block diagram shall be used.




Figure 6: Test Set-up for receiver blocking

All test procedure is carried to the section 5.4.11.2.1

RBW/VBW=8MHz/30MHz

## 12.4 Summary of Test Results/Plots

The product is receiver category 2

Hopping Mode	
Minimum Performance Criteria (@BER=0.01%) (dBm)	-88.00
P <sub>min</sub> +6dB(dBm)	-72.00
①Blocking Signal Frequency(MHz)	2380, 2503.5
①Block Signal Level (dBm)	-57.00
②Blocking Signal Frequency(MHz)	2300, 2583.5
②Block Signal Level (dBm)	-47.00
Test Result(BER):	0.002%(<0.01%)
BLE Lowest Channel (2402MHz)	
Minimum Performance Criteria (@BER=0.01%) (dBm)	-85.00
P <sub>min</sub> +6dB(dBm)	-79.00
①Blocking Signal Frequency(MHz)	2380, 2503.5
①Block Signal Level (dBm)	-57.00
②Blocking Signal Frequency(MHz)	2300, 2583.5
②Block Signal Level (dBm)	-47.00
Test Result(BER):	0.001%(<0.01%)

BLE Highest Channel (2480MHz)	
Minimum Performance Criteria (@BER=0.01%) (dBm)	-85.00
P <sub>min</sub> +6dB(dBm)	-79.00
①Blocking Signal Frequency(MHz)	2380, 2503.5
①Block Signal Level (dBm)	-57.00
②Blocking Signal Frequency(MHz)	2300, 2583.5
②Block Signal Level (dBm)	-47.00
Test Result(BER):	0.003%(<0.01%)

*\*communication link is established between the UUT and the associated companion device using the test setup shown in figure 6. While the Companion device (CMW500) adjust to a level which can obtain the minimum performance criteria BER 0.01%(this is defined by manufacturer),This level define to Pmin*

*Remark: the smallest channel bandwidth shall be used together with the lowest data rate for this channel bandwidth. This mode of operation are aligned with the performance criteria defined in clause 4.3.1.12.3 or clause 4.3.2.11.3 as declared by the manufacturer (see clause 5.4.1.t)).*

## EXHIBIT 1 - PRODUCT LABELING

### Proposed CE Label Format

**bluetooth headset**

Model: Jetblue HD1

Brand: PRYME

Importer Name: XXX

Importer Address: XXX

Shanxi Jianyu Science and technology co., LTD.

No.12 xin jin ci lu road hui jin garden 7th floor 4-201  
taiyuan city, Shanxi Province

**Specifications:** Text is Black in color and is justified. Labels are printed in indelible ink on permanent adhesive backing or silk-screened onto the EUT or shall be affixed at a conspicuous location on the EUT. The 'CE' marking must be affixed to the EUT or to its data plate. Where this is not possible or not warranted on account of the nature of the apparatus, it must be affixed to the packaging, if any, and to the accompanying documents. The 'CE' marking is allowed less than 5 mm but must clear. If the 'CE' marking is reduced or enlarged the proportions given in the above graduated drawing must be respected. The Importer name, address and Manufacturer name and address should indicate on marking label or packaging or in a document accompanying

### Proposed Label Location on EUT

CE Label Location



## EXHIBIT 2 - EUT PHOTOGRAPHS

EUT View 1



EUT View 2





EUT View 3




EUT View 4







### EUT Housing and Board View



### Solder Board-Component View 1




**Solder Board-Component View 2**

## EXHIBIT 3 - TEST SETUP PHOTOGRAPHS


### Spurious Emission Test Setup (Below 1GHz)



### Spurious Emission Test Setup (Above 1GHz)



### Extreme Conditions Test Setup



\*\*\*\*\* END OF REPORT \*\*\*\*\*